



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
015-0100-020	15	100	90	20	26	0,06		B	
015-0150-020	15	150	130	20	30	0,07		B	S
015-0200-020	15	200	180	20	30	0,08		B	S
015-0300-020	15	300	270	20	35	0,10		B	
015-0300-030	15	300	270	30	37	0,14		B	
015-0400-020	15	400	360	20	38	0,13		B	
015-0400-030	15	400	360	30	40	0,16		B	
015-0500-020	15	500	420	20	39	0,14		B	
015-0500-030	15	500	420	30	40	0,18		B	
015-0500-040	15	500	420	40	42	0,20		B	
020-0075-020	20	75	60	20	27	0,05		B	
020-0100-020	20	100	90	20	29	0,06		B	S
020-0150-050	20	150	130	20	32	0,07	X	B	S
020-0200-020	20	200	180	20	33	0,08	X	B	S
020-0200-030	20	200	180	30	33	0,11		B	S
020-0300-020	20	300	270	20	41	0,11		B	S
020-0300-030	20	300	270	30	39	0,14		B	
020-0300-040	20	300	270	40	38	0,18		B	S
020-0400-020	20	400	360	20	44	0,13		B	S
020-0400-030	20	400	360	30	45	0,17	X	B	
020-0400-040	20	400	360	40	41	0,21		B	
020-0500-020	20	500	420	20	46	0,15		B	
020-0500-030	20	500	420	30	46	0,19		B	
020-0500-040	20	500	420	40	47	0,23		B	
020-0650-020	20	650	550	20	49	0,19		B	
020-0650-030	20	650	550	30	49	0,23		B	
020-0650-040	20	650	550	40	47	0,27		B	
025-0075-020	25	75	60	20	35	0,05		B	
025-0100-020	25	100	90	20	35	0,07		B	S
025-0150-020	25	150	130	20	37	0,08		B	S
025-0200-020	25	200	180	20	39	0,09		B	S
025-0200-030	25	200	180	30	33	0,12		B	
025-0300-020	25	300	270	20	43	0,12	X	B	S
025-0300-030	25	300	270	30	39	0,15		B	S
025-0300-040	25	300	270	40	43	0,19		B	
025-0400-020	25	400	360	20	48	0,15		B	S
025-0400-030	25	400	360	30	45	0,18		B	S
025-0400-040	25	400	360	40	43	0,21		B	
025-0400-050	25	400	360	50	44	0,37		B	S
025-0500-020	25	500	420	20	54	0,18		B	
025-0500-030	25	500	420	30	47	0,22		B	S
025-0500-040	25	500	420	40	48	0,25	X	B	S
025-0500-050	25	500	420	50	43	0,41		B	
025-0650-020	25	650	550	20	60	0,23		B	
025-0650-030	25	650	550	30	58	0,26	X	B	
025-0650-040	25	650	550	40	50	0,29		B	
025-0650-050	25	650	550	50	45	0,47		B	
025-0800-020	25	800	680	20	69	0,28		B	
025-0800-030	25	800	680	30	59	0,30		B	
025-0800-040	25	800	680	40	52	0,34		B	
025-0800-050	25	800	680	50	51	0,55		B	
030-0100-020	30	100	90	20	40	0,07		B	
030-0150-020	30	150	130	20	40	0,09		B	
030-0150-030	30	150	130	30	41	0,11		B	S
030-0200-020	30	200	180	20	47	0,11		B	
030-0200-030	30	200	180	30	43	0,18		B	
030-0300-020	30	300	270	20	52	0,15		B	
030-0300-030	30	300	270	30	47	0,18	X	B	S
030-0300-040	30	300	270	40	45	0,21		B	
030-0300-050	30	300	270	50	43	0,33		B	
030-0400-030	30	400	360	30	54	0,21	X	B	S
030-0400-040	30	400	360	40	50	0,25		B	



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
030-0400-050	30	400	360	50	46	0,40		B	
030-0400-075	30	400	360	75	39	0,55		B	
030-0500-030	30	500	420	30	60	0,34		B	S
030-0500-040	30	500	420	40	55	0,49		B	S
030-0500-050	30	500	420	50	49	0,45		B	
030-0500-060	30	500	420	60	46	0,50		B	S
030-0650-030	30	650	550	30	70	0,40	X	B	
030-0650-040	30	650	550	40	65	0,55		B	
030-0650-050	30	650	550	50	54	0,55	X	B	
030-0650-060	30	650	550	60	48	0,60		B	S
030-0800-030	30	800	680	30	73	0,48	X	B	
030-0800-040	30	800	680	40	69	0,65		B	
030-0800-050	30	800	680	50	50	0,60	X	B	S
030-0800-060	30	800	680	60	48	0,70		B	
030-0800-075	30	800	680	75	55	0,70		B	
030-1000-040	30	1000	850	40	75	0,80		B	
030-1000-050	30	1000	850	50	66	0,70	X	B	S
030-1000-060	30	1000	850	60	56	0,80		B	S
030-1000-075	30	1000	850	75	61	1,30		B	
030-1250-060	30	1250	1000	60	56	1,00	X	B	S
030-1250-075	30	1250	1000	75	78	0,95		B	S
030-1500-060	30	1500	1200	60	73	1,20	X	B	
030-1500-075	30	1500	1200	75	63	1,10		B	
030-1800-100	30	1800	1400	100	66	2,40		B	
035-0100-020	35	100	80	20	44	0,07		B	
035-0150-020	35	150	120	20	49	0,10		B	
035-0150-030	35	150	120	30	48	0,12		B	
035-0200-020	35	200	160	20	52	0,12		B	
035-0200-030	35	200	160	30	48	0,14		B	
035-0200-040	35	200	160	40	45	0,17		B	
035-0300-020	35	300	240	20	60	0,17		B	
035-0300-030	35	300	240	30	53	0,19		B	
035-0300-040	35	300	240	40	48	0,23		B	
035-0300-050	35	300	240	50	50	0,33		B	S
035-0400-030	35	400	320	30	56	0,33		B	
035-0400-040	35	400	320	40	52	0,26		B	
035-0400-050	35	400	320	50	50	0,41		B	
035-0400-060	35	400	320	60	46	0,45		B	
035-0500-030	35	500	370	30	63	0,39		B	S
035-0500-040	35	500	370	40	56	0,31	X	B	
035-0500-050	35	500	370	50	55	0,47		B	S
035-0500-060	35	500	370	60	53	0,55		B	S
035-0650-040	35	650	480	40	59	0,65	X	B	
035-0350-050	35	650	480	50	60	0,55		B	
035-0650-060	35	650	480	60	55	0,65	X	B	S
035-0650-075	35	650	480	75	53	0,65		B	
035-0800-030	35	800	600	30	72	0,55		B	
035-0800-040	35	800	600	40	67	0,75		B	
035-0800-050	35	800	600	50	60	0,80		B	
035-0800-060	35	800	600	60	59	0,75		B	
035-0800-075	35	800	600	75	57	0,70		B	S
035-1000-060	35	1000	750	60	65	1,10		B	
035-1000-075	35	1000	750	75	65	0,80		B	S
035-1000-100	35	1000	750	100	67	2,00		B	
035-1250-060	35	1250	850	60	74	1,40		B	
035-1250-075	35	1250	850	75	72	1,70		B	
035-1250-100	35	1250	850	100	66	2,00		B	
040-0100-020	40	100	80	20	45	0,08		B	
040-0150-020	40	150	120	20	47	0,11		B	S
040-0150-030	40	150	120	30	54	0,16		B	S
040-0150-040	40	150	120	40	50	0,16		B	S
040-0200-020	40	200	160	20	52	0,14		B	



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
040-0200-030	40	200	160	30	55	0,21	X	B	S
040-0200-040	40	200	160	40	49	0,18		B	S
040-0200-050	40	200	160	50	48	0,29		B	
040-0300-020	40	300	240	20	63	0,19		B	
040-0300-030	40	300	240	30	58	0,29	X	B	S
040-0300-040	40	300	240	40	57	0,38		B	
040-0300-050	40	300	240	50	56	0,37	X	B	S
040-0400-030	40	400	320	30	62	0,35	X	B	S
040-0400-040	40	400	320	40	61	0,48	X	B	S
040-0400-050	40	400	320	50	60	0,43	X	B	S
040-0400-060	40	400	320	60	56	0,50		B	
040-0500-030	40	500	370	30	69	0,55	X	B	S
040-0500-040	40	500	370	40	66	0,60	X	B	S
040-0500-050	40	500	370	50	64	0,65	X	B	S
040-0500-060	40	500	370	60	58	0,60	X	B	S
040-0500-075	40	500	370	75	56	0,90		B	
040-0650-040	40	650	480	40	70	0,75		B	S
040-0650-050	40	650	480	50	67	0,75	X	B	S
040-0650-060	40	650	480	60	62	0,65	X	B	S
040-0650-075	40	650	480	75	65	1,10		B	S
040-0800-040	40	800	600	40	78	0,85		B	
040-0800-050	40	800	600	50	73	0,90		B	S
040-0800-060	40	800	600	60	67	0,80	X	B	S
040-0800-075	40	800	600	75	66	1,20		B	S
040-1000-050	40	1000	750	50	86	1,10		B	S
040-1000-060	40	1000	750	60	78	1,20	X	B	S
040-1000-075	40	1000	750	75	74	1,40		B	S
040-1000-100	40	1000	750	100	67	1,70		B	S
040-1250-050	40	1250	850	50	90	1,50		B	
040-1250-060	40	1250	850	60	86	1,60	X	B	S
040-1250-075	40	1250	850	75	83	1,80	X	B	S
040-1250-100	40	1250	850	100	74	2,10	X	B	S
040-1500-075	40	1500	1050	75	90	2,00	X	B	S
040-1500-100	40	1500	1050	100	76	2,30	X	B	S
040-1500-120	40	1500	1050	120	78	2,60		B	
040-1800-075	40	1800	1250	75	99	2,30		B	S
040-1800-100	40	1800	1250	100	82	2,60	X	B	S
040-1800-120	40	1800	1250	120	82	2,90		B	
040-2100-100	40	2100	1450	100	88	3,00		B	S
040-2100-120	40	2100	1450	120	88	3,30		B	
040-2400-100	40	2400	1650	100	93	3,20		B	
040-2400-120	40	2400	1650	120	92	3,60		B	
040-2400-150	40	2400	1650	150	90	8,00		B	
045-0200-020	45	200	160	20	64	0,14		B	
045-0200-030	45	200	160	30	60	0,21		B	
045-0200-040	45	200	160	40	58	0,32		B	
045-0300-030	45	300	240	30	67	0,38		B	
045-0300-040	45	300	240	40	62	0,41		B	S
045-0300-050	45	300	240	50	59	0,46		B	
045-0400-030	45	400	320	30	72	0,46		B	
045-0400-040	45	400	320	40	70	0,55		B	
045-0400-050	45	400	320	50	66	0,55		B	
045-0400-060	45	400	320	60	65	0,65		B	S
045-0500-040	45	500	370	40	73	0,60		B	
045-0500-050	45	500	370	50	70	0,70		B	
045-0500-060	45	500	370	60	69	0,75		B	S
045-0500-075	45	500	370	75	65	0,95		B	S
045-0650-040	45	650	480	40	81	0,80		B	S
045-0650-050	45	650	480	50	76	0,85		B	
045-0650-060	45	650	480	60	71	0,85	X	B	
045-0650-075	45	650	480	75	68	1,10		B	
045-0800-050	45	800	600	50	81	0,95	X	B	



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
045-0800-060	45	800	600	60	77	1,10		B	
045-0800-075	45	800	600	75	72	1,20		B	
045-1000-060	45	1000	750	60	83	1,20	X	B	S
045-1000-075	45	1000	750	75	77	1,50		B	S
045-1000-100	45	1000	750	100	74	1,80		B	
045-1000-120	45	1000	750	120	69	2,00		B	
045-1250-075	45	1250	850	75	84	1,80		B	
045-1250-100	45	1250	850	100	77	2,10		B	
045-1250-120	45	1250	850	120	73	2,40		B	S
045-1500-075	45	1500	1050	75	90	2,10	X	B	
045-1500-100	45	1500	1050	100	89	2,50		B	
045-1500-120	45	1500	1050	120	89	2,70		B	
045-1800-075	45	1800	1250	75	94	2,40		B	S
045-1800-100	45	1800	1250	100	92	2,70		B	
045-1800-120	45	1800	1250	120	89	3,60		B	S
045-2100-075	45	2100	1450	75	104	3,30		B	
045-2100-100	45	2100	1450	100	96	3,10		B	
045-2100-120	45	2100	1450	120	91	3,40		B	
050-0100-030	50	100	80	30	59	0,15		B	
050-0150-030	50	150	120	30	63	19,00		B	
050-0150-040	50	150	120	40	58	0,16		B	
050-0200-030	50	200	160	30	67	0,23		B	
050-0200-040	50	200	160	40	65	0,33	X	B	S
050-0200-050	50	200	160	50	60	0,31		B	
050-0300-030	50	300	240	30	72	0,38	X	B	S
050-0300-040	50	300	240	40	68	0,43		B	
050-0300-050	50	300	240	50	65	0,48		B	S
050-0300-060	50	300	240	60	64	0,55		B	S
050-0400-040	50	400	320	40	71	0,55		B	
050-0400-050	50	400	320	50	69	0,65	X	B	S
050-0400-060	50	400	320	60	69	0,55	X	B	
050-0500-040	50	500	370	40	77	0,70		B	
050-0500-050	50	500	370	50	72	0,75	X	B	S
050-0500-060	50	500	370	60	74	0,80	X	B	
050-0500-075	50	500	370	75	76	0,95		B	
050-0650-040	50	650	480	40	84	0,80		B	
050-0650-050	50	650	480	50	78	0,90	X	B	S
050-0650-060	50	650	480	60	74	0,95	X	B	S
050-0650-075	50	650	480	75	73	1,40		B	
050-0800-040	50	800	600	40	96	1,00	X	B	S
050-0800-050	50	800	600	50	89	1,10		B	
050-0800-060	50	800	600	60	86	1,30	X	B	S
050-0800-075	50	800	600	75	84	1,50	X	B	S
050-0800-100	50	800	600	100	80	1,60		B	
050-1000-050	50	1000	750	50	88	1,30		B	
050-1000-060	50	1000	750	60	86	1,40		B	
050-1000-075	50	1000	750	75	84	1,50	X	B	
050-1000-100	50	1000	750	100	80	1,80		B	
050-1000-120	50	1000	750	120	76	2,10		B	
050-1250-060	50	1250	850	60	99	2,10		B	
050-1250-075	50	1250	850	75	90	2,30	X	B	S
050-1250-100	50	1250	850	100	84	2,30	X	B	S
050-1250-120	50	1250	850	120	94	2,50		B	
050-1500-075	50	1500	1050	75	99	2,70		B	
050-1500-100	50	1500	1050	100	87	2,50	X	B	S
050-1500-120	50	1500	1050	120	84	2,90		B	
050-1800-100	50	1800	1250	100	92	2,90	X	B	S
050-1800-120	50	1800	1250	120	91	3,90	X	B	
050-1800-150	50	1800	1250	150	90	7,20		B	
050-2100-100	50	2100	1450	100	99	3,20	X	B	S
050-2100-120	50	2100	1450	120	97	3,50	X	B	S
050-2100-150	50	2100	1450	150	98	7,80		B	



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
050-2100-180	50	2100	1450	180	90	5,80		B	
050-2400-100	50	2400	1650	100	111	3,60		B	
050-2400-120	50	2400	1650	120	108	4,60	X	B	S
050-2400-150	50	2400	1650	150	106	8,50		B	
050-2400-180	50	2400	1650	180	96	6,00		B	
050-2400-200	50	2400	1650	200	108	10,50		B	
050-2700-100	50	2700	1850	100	113	3,90		B	
050-2700-120	50	2700	1850	120	112	5,20	X	B	S
050-2700-150	50	2700	1850	150	111	9,50		B	
050-2700-180	50	2700	1850	180	105	10,50		B	
050-3000-120	50	3000	2100	120	120	5,60		B	
050-3000-150	50	3000	2100	150	123	9,50		B	
050-3000-180	50	3000	2100	180	1160	11,00		B	
055-0150-030	55	150	120	30	68	0,25		B	S
055-0150-040	55	150	120	40	66	0,28		B	
055-0200-040	55	200	160	40	68	0,35		B	
055-0200-050	55	200	160	50	64	0,32	X	B	
055-0300-040	55	300	240	40	74	0,46		B	
055-0300-050	55	300	240	50	68	0,85	X	B	S
055-0300-060	55	300	240	60	60	0,45		B	
055-0400-040	55	400	320	40	77	0,6		B	
055-0400-050	55	400	320	50	72	0,65	X	B	S
055-0400-060	55	400	320	60	69	0,55		B	
055-0500-040	55	500	370	40	74	0,75	X	B	S
055-0500-050	55	500	370	50	75	0,75	X	B	S
055-0500-060	55	500	370	60	74	0,65	X	B	S
055-0500-075	55	500	370	75	77	1,20	X	B	
055-0650-040	55	650	480	40	84	0,90	X	B	S
055-0650-050	55	650	480	50	80	0,75	X	B	S
055-0650-060	55	650	480	60	79	1,00	X	B	S
055-0650-075	55	650	480	75	83	1,20	X	B	S
055-0800-040	55	800	600	40	93	1,10		B	
055-0800-050	55	800	600	50	85	1,10		B	S
055-0800-060	55	800	600	60	83	1,20	X	B	S
055-0800-075	55	800	600	75	86	1,40	X	B	S
055-0800-100	55	800	600	100	80	1,70		B	
055-1000-050	55	1000	750	50	100	1,40		B	
055-1000-060	55	1000	750	60	93	1,40	X	B	S
055-1000-075	55	1000	750	75	91	1,90	X	B	S
055-1000-100	55	1000	750	100	83	1,90		B	S
055-1000-120	55	1000	750	120	79	2,10		B	
055-1250-060	55	1250	850	60	106	2,20		B	
055-1250-075	55	1250	850	75	98	2,60	X	B	S
055-1250-100	55	1250	850	100	88	2,40		B	S
055-1250-120	55	1250	850	120	84	2,60		B	S
055-1500-075	55	1500	1050	75	104	3,00		B	
055-1500-100	55	1500	1050	100	96	2,60		B	
055-1500-120	55	1500	1050	120	91	2,90		B	S
055-1800-100	55	1800	1250	100	105	3,70	X	B	S
055-1800-120	55	1800	1250	120	96	3,30		B	
055-1800-150	55	1800	1250	150	92	7,60		B	
055-2100-100	55	2100	1450	100	118	5,80		B	
055-2100-120	55	2100	1450	120	105	3,70		B	
055-2100-150	55	2100	1450	150	95	7,80		B	
055-2100-180	55	2100	1450	180	91	9,50		B	
055-2400-100	55	2400	1650	100	122	6,20		B	
055-2400-120	55	2400	1650	120	111	5,00		B	
055-2400-150	55	2400	1650	150	108	8,50		B	
055-2400-180	55	2400	1650	180	96	6,20		B	
055-2400-200	55	2400	1650	200	94	11,00		B	
055-2700-100	55	2700	1850	100	138	8,50		B	
055-2700-120	55	2700	1850	120	120	5,60		B	



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
055-2700-150	55	2700	1850	150	116	9,50		B	
055-2700-180	55	2700	1850	180	121	10,50		B	
055-2700-200	55	2700	1850	200	115	11,50		B	
055-3000-120	55	3000	2100	120	125	6,00		B	
055-3000-150	55	3000	2100	150	121	10,00		B	
055-3000-180	55	3000	2100	180	121	11,50		B	
055-3000-200	55	3000	2100	200	116	12,00		B	
060-0150-030	60	150	100	30	75	0,26	X	B	S
060-0150-040	60	150	100	40	71	0,29		B	
060-0150-050	60	150	100	50	69	0,27		B	
060-0200-030	60	200	140	30	80	0,55		B	S
060-0200-040	60	200	140	40	78	0,36		B	
060-0200-050	60	200	140	50	74	0,34		B	
060-0300-030	60	300	210	30	84	0,75		B	S
060-0300-040	60	300	210	40	82	0,48		B	
060-0300-050	60	300	210	50	80	0,55		B	
060-0300-060	60	300	210	60	78	0,60		B	
060-0400-040	60	400	280	40	83	0,65		B	
060-0400-050	60	400	280	50	80	0,70		B	S
060-0400-060	60	400	280	60	78	0,70		B	S
060-0500-040	60	500	350	40	88	0,75		B	S
060-0500-050	60	500	350	50	84	0,80	X	B	S
060-0500-060	60	500	350	60	81	1,00		B	
060-0500-075	60	500	350	75	82	1,00		B	
060-0650-050	60	650	420	50	96	1,10	X	B	
060-0650-060	60	650	420	60	86	1,10	X	B	
060-0650-075	60	650	420	75	85	1,50	X	B	
060-0650-100	60	650	420	100	79	1,50		B	S
060-0800-060	60	80	520	60	99	1,60	X	B	S
060-0800-075	60	800	520	75	92	1,70		B	S
060-0800-100	60	800	520	100	84	1,70		B	S
060-1000-060	60	1000	650	60	105	1,80	X	B	S
060-1000-075	60	1000	650	75	102	2,10		B	S
060-1000-100	60	1000	650	100	89	1,90		B	S
060-1000-120	60	1000	650	120	84	2,10		B	S
060-1250-060	60	1250	800	60	114	2,50		B	
060-1250-075	60	1250	800	75	109	2,70	X	B	S
060-1250-100	60	1250	800	100	100	2,40	X	B	S
060-1250-120	60	1250	800	120	94	2,70		B	
060-1250-150	60	1250	800	150	92	6,20		B	
060-1500-075	60	1500	950	75	109	3,10	X	B	S
060-1500-100	60	1500	950	100	104	2,90	X	B	S
060-1500-120	60	1500	950	120	100	3,00		B	
060-1500-150	60	1500	950	150	102	7,00		B	
060-1800-100	60	1800	1150	100	109	3,30	X	B	S
060-1800-120	60	1800	1150	120	106	4,20		B	
060-1800-150	60	1800	1150	150	105	7,60		B	
060-2100-100	60	2100	1350	100	123	4,40		B	
060-2100-120	60	2100	1350	120	115	4,80	X	B	
060-2100-150	60	2100	1350	150	113	8,50		B	
060-2100-180	60	2100	1350	180	107	10,00		B	
060-2400-120	60	2000	1550	120	119	5,20	X	B	S
060-2400-150	60	2400	1550	150	118	9,00		B	
060-2400-180	60	2400	1550	180	109	10,00		B	
060-2400-200	60	2400	1550	200	106	11,00		B	
060-2700-120	60	2700	1750	120	125	5,80	X	B	S
060-2700-150	60	2700	1750	150	125	10,00		B	
060-2700-180	60	2700	1750	180	116	11,00		B	
060-2700-200	60	2700	1750	200	110	11,50		B	
060-3000-120	60	3000	1950	120	130	6,20		B	S
060-3000-150	60	3000	1950	150	126	10,50		B	
060-3000-180	60	3000	1950	180	123	11,50		B	



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
060-3000-200	60	3000	1950	200	120	12,50		B	
065-0150-030	65	150	100	30	81	0,27		B	S
065-0150-040	65	150	100	40	77	0,00		B	
065-0200-030	65	200	140	30	78	0,34		B	
065-0200-040	65	200	140	40	74	0,38		B	
065-0200-050	65	200	140	50	79	0,44		B	
065-0300-030	65	300	210	30	83	0,50		B	S
065-0300-040	65	300	210	40	78	0,50		B	
065-0300-050	65	300	210	50	75	0,60	X	B	S
065-0300-060	65	300	210	60	72	0,75		B	
065-0400-030	65	400	280	30	90	0,65		B	
065-0400-040	65	400	280	40	90	0,70		B	
065-0400-050	65	400	280	50	88	1,20	X	B	S
065-0400-060	65	400	280	60	84	0,90		B	
065-0500-050	65	500	350	50	94	1,40		B	
065-0500-060	65	500	350	60	91	1,10	X	B	S
065-0650-050	65	650	420	50	103	1,70		B	
065-0650-060	65	650	420	60	94	1,30	X	B	S
065-0650-075	65	650	420	75	97	1,60		B	
065-0650-100	65	650	420	100	88	1,50		B	
065-0800-060	65	800	520	60	106	1,60		B	S
065-0800-075	65	800	520	75	96	1,80	X	B	S
065-0800-100	65	800	520	100	89	1,70		B	
006-5100-075	65	1000	650	75	102	2,10		B	S
065-1000-100	65	1000	650	100	92	2,10		B	S
065-1000-120	65	1000	650	120	89	2,60		B	
065-1250-075	65	1250	800	75	113	2,80		B	S
065-1250-100	65	1250	800	100	103	3,10		B	S
065-1250-120	65	1250	800	120	98	3,50		B	
065-1250-150	65	1250	800	150	96	6,40		B	
065-1500-075	65	1500	950	75	113	3,30		B	S
065-1500-100	65	1500	950	100	108	3,60		B	S
065-1500-100	65	1500	950	120	100	3,90		B	S
065-1500-150	65	1500	950	150	99	7,00		B	
065-1800-100	65	1800	1150	100	118	4,20		B	S
065-1800-120	65	1800	1150	120	108	4,60	X	B	S
065-1800-150	65	1800	1150	150	105	7,80		B	
065-2100-100	65	2100	1350	100	126	6,40		B	S
065-2100-120	65	2100	1350	120	116	5,00		B	
065-2100-150	65	2100	1350	150	114	8,50		B	
065-2100-180	65	2100	1350	180	103	6,00		B	
065-2400-120	65	2400	1350	120	132	5,80		B	
065-2400-150	65	2400	1550	150	128	9,50		B	
065-2400-180	65	2400	1550	180	117	6,60		B	
065-2400-200	65	2400	1550	200	113	11,50		B	
065-2700-120	65	2700	1750	120	133	6,40		B	
065-2700-150	65	2700	1750	150	136	10,50		B	
065-2700-180	65	2700	1750	180	126	7,00		B	
065-2700-200	65	2700	1750	200	121	12,50		B	
065-3000-120	65	3000	1950	120	130	9,50		B	
065-3000-150	65	3000	1950	150	142	11,00		B	
065-3000-180	65	3000	1950	180	135	12,50		B	
065-3000-200	65	3000	1950	200	130	13,00		B	
070-0150-030	70	150	100	30	85	0,29		B	S
070-0150-040	70	150	100	40	82	0,31		B	
070-0200-030	70	200	140	30	88	0,60		B	S
070-0200-040	70	200	140	40	100	0,40		B	
070-0200-050	70	200	140	50	88	0,46		B	
070-0300-030	70	300	210	30	93	0,55		B	S
070-0300-040	70	300	210	40	91	0,60		B	
070-0300-050	70	300	210	50	90	0,95		B	S
070-0300-060	70	300	210	60	87	0,80		B	



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
070-0400-030	70	400	280	30	100	0,70		B	S
070-0400-040	70	400	280	40	96	0,75		B	
070-0400-040	70	400	280	50	93	1,30	X	B	S
070-0400-060	70	400	280	60	90	0,95		B	
070-0500-050	70	500	350	50	101	1,50		B	S
070-0500-060	70	500	350	60	93	1,20	X	B	
070-0650-050	70	650	420	50	100	1,80		B	S
070-0650-060	70	650	420	60	100	1,40	X	B	S
070-0650-075	70	650	420	75	96	1,60	X	B	S
070-0650-100	70	650	420	100	90	1,60		B	
070-0800-060	70	800	520	60	109	1,70	X	B	S
070-0800-075	70	800	520	75	105	2,50	X	B	S
070-0800-100	70	800	520	100	100	1,80	X	B	S
070-1000-075	70	1000	650	75	108	3,10	X	B	S
070-1000-100	70	1000	650	100	103	2,60	X	B	S
070-1000-120	70	1000	650	120	99	2,90		B	
070-1250-075	70	1250	800	75	118	4,00		B	S
070-1250-100	70	1250	800	100	113	3,20	X	B	S
070-1250-120	70	1250	800	120	114	3,60	X	B	
070-1250-150	70	1250	800	150	111	6,40	X	B	
070-1500-075	70	1500	950	75	128	4,60		B	
070-1500-100	70	1500	950	100	118	5,00		B	S
070-1500-120	70	1500	950	120	115	4,00	X	B	S
070-1500-150	70	1500	950	150	116	7,20	X	B	
070-1800-100	70	1800	1150	100	125	5,80		B	S
070-1800-120	70	1800	1150	120	123	6,20		B	S
070-1800-150	70	1800	1150	150	116	8,00	X	B	
070-2100-100	70	2100	1350	100	136	6,60		B	S
070-2100-120	70	2100	1350	120	134	7,20		B	S
070-2100-150	70	2100	1350	150	123	9,00	X	B	
070-2100-180	70	2100	1350	180	118	10,00		B	S
070-2400-120	70	2400	1550	120	145	8,00		B	
070-2400-150	70	2400	1550	150	142	9,50	X	B	
070-2400-180	70	2400	1550	180	137	11,00		B	S
070-2400-200	70	2400	1550	200	132	11,50		B	
070-2700-120	70	2700	1750	120	153	9,00		B	
070-2700-150	70	2700	1750	150	142	10,50	X	B	
070-2700-180	70	2700	1750	180	133	11,50		B	S
070-2700-200	70	2700	1750	200	130	12,50		B	
070-3000-120	70	3000	1950	120	160	9,50		B	
070-3000-150	70	3000	1950	150	161	11,50	X	B	
070-3000-180	70	3000	1950	180	149	12,50		B	S
070-3000-200	70	3000	1950	200	137	13,00		B	
075-0150-040	75	150	100	40	86	0,33		B	
075-0200-040	75	200	140	40	84	0,42		B	
075-0200-050	75	200	140	50	83	0,70		B	
075-0300-040	75	300	210	40	99	0,60		B	
075-0300-050	75	300	210	50	95	1,00		B	S
075-0300-060	75	300	210	60	90	0,85		B	
075-0400-040	75	400	280	40	103	0,75		B	
075-0400-050	75	400	280	50	100	1,20	X	B	S
075-0400-060	75	400	280	60	94	1,00		B	
075-0500-050	75	500	350	50	107	1,50	X	B	S
075-0500-060	75	500	350	60	99	1,20		B	S
075-0650-050	75	650	420	50	117	1,90	X	B	
075-0650-060	75	650	420	60	105	1,50		B	S
075-0650-075	75	650	420	75	102	2,20		B	S
075-0650-100	75	650	420	100	100	2,70		B	S
075-0800-060	75	800	520	60	117	1,70		B	S
075-0800-075	75	800	520	75	111	2,50		B	S
075-0800-100	75	800	520	100	104	2,10		B	S
075-1000-075	75	1000	650	75	114	3,10	X	B	S



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
075-1000-100	75	1000	650	100	110	3,30	X	B	S
075-1000-120	75	1000	650	120	107	2,80		B	S
075-1250-075	75	1250	800	75	126	4,00		B	S
075-1250-100	75	1250	800	100	115	4,40	X	B	S
075-1250-120	75	1250	800	120	113	3,60		B	
075-1500-100	75	1500	950	100	120	5,20	X	B	S
075-1500-120	75	1500	950	120	115	4,40		B	S
075-1500-150	75	1500	950	150	118	7,00		B	
075-1800-100	75	1800	1150	100	130	5,80	X	B	S
075-1800-120	75	1800	1150	120	124	4,80		B	S
075-1800-150	75	1800	1150	150	123	8,50		B	
075-2100-100	75	2100	1350	100	142	6,80		B	S
075-2100-120	75	2100	1350	120	138	7,40	X	B	S
075-2100-150	75	2100	1350	150	136	9,50		B	
075-2400-120	75	2400	1550	120	137	8,00	X	B	S
075-2400-150	75	2400	1550	150	142	9,50		B	
075-2700-120	75	2700	1750	120	147	9,00		B	S
075-2700-150	75	2700	1750	150	150	10,50		B	
075-2700-180	75	2700	1750	180	144	12,00		B	
075-3000-120	75	3000	1950	120	152	10,00		B	S
075-3000-150	75	3000	1950	150	154	11,50		B	
075-3000-180	75	3000	1950	180	148	12,50		B	S
080-0200-050	80	200	140	50	105	0,75		B	
080-0300-050	80	300	210	50	103	1,10		B	S
080-0300-060	80	300	210	60	102	0,85		B	
080-0400-050	80	400	280	50	110	1,30		B	S
080-0400-060	80	400	280	60	100	1,10		B	
080-0500-050	80	500	350	50	115	1,60	X	B	S
080-0500-060	80	500	350	60	104	1,30	X	B	S
080-0500-075	80	500	350	75	99	1,90	X	B	
080-0650-060	80	650	420	60	111	1,60	X	B	S
080-0650-075	80	650	420	75	105	1,70	X	B	S
080-0650-100	80	650	420	100	100	2,00		B	
080-0800-075	80	800	520	75	112	2,60	X	B	S
080-0800-100	80	800	520	100	106	2,90	X	B	
080-1000-075	80	1000	650	75	123	3,20	X	B	S
080-1000-100	80	1000	650	100	116	2,70	X	B	S
080-1000-120	80	1000	650	120	112	2,90		B	S
080-1250-075	80	1250	800	75	132	4,20		B	S
080-1250-100	80	1250	800	100	125	4,60	X	B	S
080-1250-120	80	1250	800	120	112	3,70		B	S
080-1500-100	80	1500	950	100	128	3,90	X	B	S
080-1500-120	80	1500	950	120	133	5,80		B	S
080-1800-100	80	1800	1150	100	134	6,40		B	S
080-1800-120	80	1800	1150	120	130	6,80		B	S
080-1800-150	80	1800	1150	150	134	8,50		B	
080-2100-120	80	2100	1350	120	138	7,60	X	B	S
080-2100-150	80	2100	1350	150	146	9,50		B	
080-2400-120	80	2400	1550	120	142	8,50	X	B	S
080-2400-150	80	2400	1550	150	146	10,50		B	
080-2400-180	80	2400	1550	180	139	11,00		B	
080-2400-200	80	2400	1550	200	133	12,00		B	
080-2700-120	80	2700	1750	120	162	9,50	X	B	S
080-2700-150	80	2700	1750	150	153	11,50		B	
080-2700-180	80	270	1750	180	149	12,50		B	
080-2700-200	80	2700	1750	200	137	13,00		B	
080-3000-120	80	3000	1950	120	148	10,50	X	B	
080-3000-150	80	3000	1950	150	159	12,00		B	
080-3000-180	80	3000	1950	180	152	13,00		B	
080-3000-200	80	3000	1950	200	154	14,00		B	
090-0300-060	90	300	210	60	115	0,90		B	
090-0400-060	90	400	280	60	116	1,10	X	B	S



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
090-0400-075	90	400	280	75	115	1,70	X	B	S
090-0500-060	90	500	350	60	121	1,30	X	B	
090-0500-075	90	500	350	75	120	2,00	X	B	S
090-0650-060	90	650	420	60	128	1,70		B	
090-0650-075	90	650	420	75	125	2,40		B	S
090-0650-100	90	650	420	100	120	2,90	X	B	S
090-0800-075	90	800	520	75	133	3,00	X	B	S
090-0800-100	90	800	520	100	119	3,30	X	B	S
090-1000-075	90	1000	650	75	135	3,60		B	S
090-1000-100	90	1000	650	100	123	2,80	X	B	S
090-1250-100	90	1250	800	100	132	5,20	X	B	S
090-1250-120	90	1250	800	120	125	5,40		B	S
090-1500-100	90	1500	950	100	144	5,80	X	B	S
090-1500-120	90	1500	950	120	130	6,40	X	B	S
090-1500-150	90	1500	950	150	140	7,80		B	
090-1800-100	90	1800	1150	100	162	6,80	X	B	
090-1800-120	90	1800	1150	120	137	7,20		B	
090-1800-150	90	1800	1150	150	145	9,00		B	
090-2100-120	90	2100	1350	120	156	8,50	X	B	S
090-2100-150	90	2100	1350	150	154	10,00		B	
090-2400-120	90	2400	1550	120	165	9,50	X	B	
090-2400-150	90	2400	1550	150	156	11,00		B	
090-2400-180	90	2400	1550	180	150	12,00		B	S
090-2700-120	90	2700	1750	120	172	10,50	X	B	
090-2700-150	90	2700	1750	150	159	12,00		B	
090-2700-180	90	2700	1750	180	155	13,00		B	
090-3000-150	90	3000	1950	150	166	13,00		B	
090-3000-180	90	3000	1950	180	164	14,00		B	S
090-3000-200	90	3000	1950	200	159	14,50		B	
100-0200-075	100	200	140	75	116	1,30		B	S
100-0300-075	100	300	210	75	120	1,60		B	S
100-0400-075	100	400	280	75	122	1,80		B	S
100-0500-075	100	500	350	75	128	1,60	X	B	
100-0500-100	100	500	350	100	123	1,90		B	S
100-0650-075	100	650	420	75	135	2,80	X	B	S
100-0650-100	100	650	420	100	128	2,20		B	
100-0650-120	100	650	420	120	126	3,10		B	
100-0800-075	100	800	520	75	138	3,20		B	S
100-0800-100	100	800	520	100	127	2,60		B	S
100-0800-120	100	800	520	120	131	3,70		B	
100-1000-100	100	1000	650	100	135	4,20		B	S
100-1000-120	100	1000	650	120	135	4,40		B	S
100-1250-100	100	1250	800	100	144	5,40	X	B	S
100-1250-120	100	1250	800	120	135	5,80	X	B	
100-1500-100	100	1500	950	100	146	6,40	X	B	S
100-1500-120	100	1500	950	120	140	6,60		B	
100-1500-150	100	1500	950	150	138	8,00		B	
100-1800-100	100	1800	1150	100	162	7,60	X	B	
100-1800-120	100	1800	1150	120	151	7,80	X	B	S
100-1800-150	100	1800	1150	150	147	9,50		B	S
100-2100-150	100	2100	1350	150	164	11,00		B	
100-2100-180	100	2100	1350	180	149	11,50		B	
100-2100-200	100	2100	1350	200	146	12,50		B	
100-2400-150	100	2400	1550	150	163	12,00		B	
100-2400-180	100	2400	1550	180	152	13,00		B	
100-2400-200	100	2400	1550	200	145	13,50		B	S
100-2700-150	100	2700	1750	150	183	13,50		B	
100-2700-180	100	2700	1750	180	168	14,50		B	
100-2700-200	100	2700	1750	200	157	14,50		B	S
100-3000-150	100	3000	1950	150	183	14,50		B	
100-3000-180	100	3000	1950	180	172	15,00		B	
100-3000-200	100	3000	1950	200	161	16,00		B	



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
110-0200-075	110	200	140	75	128	1,30		B	
110-0300-075	110	300	210	75	131	1,70		B	
110-0400-075	110	400	280	75	135	1,90		B	S
110-0500-075	110	500	350	75	141	2,30		B	
110-0500-100	110	500	350	100	130	2,60	X	B	
110-0650-075	110	650	420	75	150	2,90		B	S
110-0650-100	110	650	420	100	139	3,20	X	B	S
110-0800-075	110	800	520	75	160	3,40	X	B	S
110-0800-100	110	800	520	100	134	3,70		B	S
110-1000-100	110	1000	650	100	149	4,40		B	S
110-1000-120	110	1000	650	120	140	5,80		B	S
110-1250-100	110	1250	800	100	156	5,80	X	B	S
110-1250-120	110	1250	800	120	151	6,20		B	S
110-1250-150	110	1250	800	150	149	7,20	X	B	
110-1250-180	110	1250	800	180	146	8,50		B	
110-1250-200	110	1250	800	200	145	9,50		B	
110-1500-120	110	1500	950	120	160	7,00		B	S
110-1500-150	110	1500	950	150	152	8,50		B	
110-1500-200	110	1500	950	200	142	10,00		B	
110-1800-150	110	1800	1150	150	167	10,50		B	
110-1800-180	110	1800	1150	180	161	11,00		B	
110-1800-200	110	1800	1150	200	152	11,50		B	
110-2100-150	110	2100	1350	150	160	11,50		B	
110-2100-180	110	2100	1350	180	159	12,00		B	
110-2100-200	110	2100	1350	200	159	13,00		B	
110-2400-150	110	2400	1550	150	168	12,50		B	
110-2400-180	110	2400	1550	180	162	13,50		B	
110-2400-200	110	2400	1550	200	159	14,50		B	
110-2700-150	110	2700	1750	150	179	14,00		B	
110-2700-180	110	2700	1750	180	172	15,00		B	
110-2700-200	110	2700	1750	200	170	15,00		B	S
110-3000-180	110	3000	1950	180	174	16,50		B	
110-3000-200	110	3000	1950	200	176	22,50		B	S
120-0400-075	120	400	280	75	145	2,00		B	S
120-0500-075	120	500	350	75	150	2,40		B	S
120-0500-100	120	500	350	100	143	2,80		B	
120-0650-075	120	650	420	75	158	3,10	X	B	
120-0650-100	120	650	420	100	147	3,30		B	
120-0800-075	120	800	520	75	164	3,60		B	
120-0800-100	120	800	520	100	148	3,90	X	B	S
120-1000-100	120	1000	650	100	157	4,60		B	S
120-1000-120	120	1000	650	120	153	4,80		B	
120-1250-120	120	1250	800	120	161	6,60		B	S
120-1250-150	120	1250	800	150	157	7,60		B	
120-1250-180	120	1250	800	180	154	9,00		B	
120-1250-200	120	1250	800	200	151	9,50		B	
120-1500-120	120	1500	950	120	162	7,40		B	S
120-1500-150	120	1500	950	150	161	8,50		B	
120-1500-200	120	1500	950	200	156	10,00		B	
120-1800-120	120	1800	1150	120	173	9,00		B	S
120-1800-150	120	1800	1150	150	165	10,50		B	
120-1800-180	120	1800	1150	180	158	11,00		B	
120-1800-200	120	1800	1150	200	159	11,50		B	S
120-2100-120	120	2100	1350	120	177	10,50		B	
120-2100-150	120	2100	1350	150	171	11,50		B	
120-2100-180	120	2100	1350	180	167	12,00		B	
120-2100-200	120	2100	1350	200	164	13,00		B	S
120-2400-180	120	2400	1550	180	173	13,50		B	
120-2400-200	120	2400	1550	200	170	14,50		B	
120-2700-180	120	2700	1750	180	178	15,00		B	
120-2700-200	120	2700	1750	200	181	20,50		B	
120-3000-180	120	3000	1950	180	184	16,00		B	



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
120-3000-200	120	3000	1950	200	186	22,50		B	
120-3500-180	120	3500	2200	180	191	18,50		B	
120-3500-200	120	3500	2200	200	195	25,50		B	
130-0650-100	130	650	420	100	169	4,40		B	
130-0650-120	130	650	420	120	160	3,90		B	
130-0800-120	130	800	520	120	168	4,40	X	B	S
130-1000-120	130	1000	650	120	172	5,40		B	S
130-1000-150	130	1000	650	150	160	6,20		B	
130-1250-120	130	1250	800	120	178	7,00		B	
130-1250-150	130	1250	800	150	172	8,50		B	
130-1250-180	130	1250	800	180	166	9,00		B	
130-1250-200	130	1250	800	200	163	10,00		B	
130-1500-150	130	1500	950	150	175	9,50		B	S
130-1500-200	130	1500	950	200	164	10,50		B	
130-1800-150	130	1800	1150	150	184	11,00		B	
130-1800-180	130	1800	1150	180	178	12,00		B	
130-1800-200	130	1800	1150	200	181	16,00		B	
130-2100-150	130	2100	1350	150	192	12,00		B	
130-2100-180	130	2100	1350	180	185	13,00		B	
130-2100-200	130	2100	1350	200	189	18,00		B	
130-2400-180	130	2400	1550	180	191	14,50		B	
130-2400-200	130	2400	1550	200	195	20,00		B	
140-0650-100	140	650	420	100	179	4,80		B	
140-0300-120	140	650	420	120	170	3,80		B	S
140-0800-120	140	800	520	120	177	4,60		B	S
140-1000-120	140	1000	650	120	192	5,40		B	
140-1000-150	140	1000	650	150	170	6,60		B	
140-1250-120	140	1250	800	120	200	7,40		B	
140-1250-150	140	1250	800	150	189	8,50		B	
140-1500-150	140	1500	950	150	183	9,50	X	B	
140-1800-150	140	1800	1150	150	190	11,00		B	
140-1800-180	140	1800	1150	180	1850	12,00		B	
140-1800-200	140	1800	1150	200	190	16,00		B	
140-2100-180	140	2100	1350	180	195	13,00		B	
140-2100-200	140	2100	1350	200	199	18,00		B	
145-0300-100	145	300	210	100	176	2,80		B	
145-0300-120	145	300	210	120	170	2,40		B	
145-0500-100	145	500	350	100	186	4,00		B	
145-0500-120	145	500	350	120	180	3,50		B	S
150-0200-100	150	200	140	100	168	2,40		B	
150-0400-075	150	400	280	75	177	2,40		B	S
150-0400-100	150	400	280	100	174	3,20		B	
150-0400-120	150	400	280	120	166	2,10		B	
150-0500-100	150	500	350	100	182	4,20		B	
150-0500-120	150	500	350	120	175	3,50		B	
150-0650-100	150	650	420	100	189	5,00		B	
150-0650-120	150	650	420	120	178	4,00		B	S
150-0800-100	150	800	520	100	186	6,00		B	
150-0800-120	150	800	520	120	182	4,80		B	S
150-1000-150	150	1000	650	150	181	6,80		B	
150-1000-180	150	1000	650	180	175	7,20		B	
150-1000-200	150	1000	650	200	178	10,50		B	
150-1250-150	150	1250	800	150	190	8,50		B	
150-1250-180	150	1250	800	180	184	9,50		B	
150-1250-200	150	1250	800	200	187	13,50		B	
150-1500-180	150	1500	950	180	189	10,50		B	
150-1500-200	150	1500	950	200	192	15,50		B	
150-1800-180	150	1800	1150	180	194	12,00		B	
150-1800-200	150	1800	1150	200	197	16,50		B	
150-2100-200	150	2100	1350	200	206	18,50		B	
155-0650-100	155	650	420	100	194	5,20		B	
155-0800-100	155	800	520	100	201	6,00		B	



WMB - Spiralenprogramm / WMB spiral-range



Typ	D1 [mm]	Auszug in mm		ZD [mm]	D2 [mm]	Masse [kg] (ca.)	geeignet f. nachträgl. Einbau	Material	
		vertikal	horizontal					blaupoliert	rostfrei
155-0800-120	155	800	520	120	190	5,00		B	
155-1000-150	155	1000	650	150	190	7,00		B	
160-0400-100	160	400	280	100	184	3,40		B	
160-0400-120	160	400	280	120	178	2,90		B	
160-0500-100	160	500	350	100	190	4,20		B	
160-0500-120	160	500	350	120	185	3,70		B	S
160-0500-120	160	500	350	150	178	4,40		B	S
160-0650-120	160	650	420	120	188	4,20		B	S
160-0650-150	160	650	420	150	185	5,40		B	S
160-0650-180	160	650	420	180	181	6,20		B	
160-0800-150	160	800	520	150	188	6,00		B	
160-0800-200	160	800	520	200	180	7,00		B	
160-1000-150	160	1000	650	150	195	7,00		B	
160-1000-180	160	1000	650	180	187	8,00		B	
160-1000-200	160	1000	650	200	188	11,00		B	
160-1250-180	160	1250	800	180	195	9,50		B	
160-1250-200	160	1250	800	200	198	13,50		B	
160-1500-180	160	1500	950	180	201	11,00		B	
160-1500-200	160	1500	950	200	206	16,00		B	
160-1800-200	160	1800	1150	200	214	18,00		B	
170-0400-120	170	400	280	120	186	3,00		B	
170-0650-120	170	650	420	120	197	4,40		B	S
170-0650-150	170	650	420	150	190	5,60		B	S
170-0650-180	170	650	420	180	189	6,20		B	
170-0800-150	170	800	520	150	198	6,20		B	
170-0800-200	170	800	520	150	191	7,20		B	
170-1000-150	170	1000	650	150	205	7,20		B	
170-1000-180	170	1000	650	180	201	8,50		B	
170-1000-200	170	1000	650	200	200	9,00		B	
170-1250-180	170	1250	800	180	205	10,00		B	
170-1250-200	170	1250	800	200	205	11,00		B	
170-1500-200	170	1500	950	200	216	16,50		B	
190-0650-150	190	650	420	150	221	5,80		B	
190-0650-200	190	650	420	200	220	9,50		B	
190-0800-150	190	800	520	150	224	6,40		B	
190-0800-200	190	800	520	200	225	10,50		B	
190-1000-150	190	1000	650	150	226	7,80		B	
190-1000-200	190	1000	650	200	229	11,50		B	
210-0650-200	210	650	420	200	231	9,00		B	